

EQQ LiteRex BK

Installation cable HF

300/500 V



For Fixed installations indoors and outdoors. Not to be laid in soil nor directly in cast concrete. UV-protected outer sheath and core insulation.

Additional information	Flame retardant EN 60332-3-23, halogen free EN 60754 and minimal smoke production EN 61034
Standards	SS 424 02 19-5:2014
Reaction to fire	Dca-s2,d2,a2
Conductor	Circular solid copper, EN/IEC 60228 class 1
Insulation	Halogen free UV-resistant polyethylene
Core Identification	Blue, brown Yellow-green, blue, brown Yellow-green, blue, brown, black Yellow-green, blue, brown, black, grey
Oversheath	Halogen free UV-resistant polyolefin compound , White
Size	3G2,5
Product code	1254903
Voltage	300/500 V
Nominal diameter of complete cable mm	9
Nominal weight of cable kg/km	130
Min. bending radius, handling mm	90
Min. bending radius, final bending mm	27
Max. pulling force by pulling-eye kN	0.38
Maximum DC resistance at 20 °C Ω/km	7.41
Min. cable temperature during handling °C	-15
Max. conductor temperature °C	70
Max. cond. temp. short circuit max. 5 s °C	160
standard packing m	Bundle 50
Electricity number	6438176227725
EAN code	6438176227725

