


## AEMCMK-HF C

Aluminum power cable EMC

0.6/1 (1.2) kV



For fixed installations indoors and outdoors. Collective screen gives an excellent protection against electromagnetic radiation from the cable.

<b>Standards</b>	SFS 5546:2020, SS 424 14 18:2007, HD 604 S1:1994/A3:2005 Part 5 Section I and D, IEC 60502-1:2004
<b>Reaction to fire</b>	Cca-s1,d1,a1
<b>Conductor</b>	Sector shaped, stranded aluminium, EN/IEC 60228 class 2
<b>Insulation</b>	Halogen free XLPE
<b>Core Identification</b>	brown, black, grey blue, brown, black, grey
<b>Oversheath</b>	UV-protected halogen free polyolefin compound , Black
<b>Size</b>	3x300/88
<b>Product code</b>	1149290
<b>Voltage</b>	0.6/1 (1.2) kV
<b>Nominal diameter of complete cable mm</b>	56
<b>Nominal weight of cable kg/km</b>	4560
<b>Min. bending radius, handling mm</b>	668
<b>Min. bending radius, final bending mm</b>	468
<b>Max. pulling force by pulling-eye kN</b>	13.5
<b>Maximum DC resistance at 20 °C Ω/km</b>	0.1
<b>Min. cable temperature during handling °C</b>	-15
<b>Max. conductor temperature °C</b>	90
<b>Max. cond. temp. short circuit max. 5 s °C</b>	250
<b>standard packing m</b>	Drum 1000
<b>Electricity number</b>	6438176302927
<b>EAN code</b>	6438176302927

