

## AXMK/PE PoweRex PE

### Aluminium power cable

### 0,6/1 (1,2) kV



### Application

Aluminium power cable for fixed installations outdoors. May be buried directly in soil, also by ploughing. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free, but without fire protection. The cable is not CPR-classified.

### Design

<b>Standards</b>	SFS 5800, SEK TS 424 14 18-1, HD 603 5 E & O
<b>Certificates</b>	SGS Fimko FI 41546
<b>Product Environmental Profile (PEP/EPD)</b>	PEP NXNS-00450-V01.01-EN
<b>Conductor</b>	16-25 mm <sup>2</sup> circular stranded aluminium, EN/IEC 60228 class 2 35-300 mm <sup>2</sup> sector shaped, stranded aluminium, EN/IEC 60228 class 2
<b>Insulation</b>	UV-protected cross-linked polyethylene XLPE
<b>Core Identification</b>	Yellow-green, brown, black, grey
<b>Inner covering</b>	Plastic tape
<b>Oversheath</b>	UV-protected polyethylene compound PELLD , Black
<b>Rip cord</b>	Aramid cord

### Temperature limits

<b>Max. conductor temperature °C</b>	90
<b>Max. cond. temp. short circuit max. 5 s °C</b>	250
<b>Min. cable temperature during operation °C</b>	-50
<b>Min. cable temperature during handling °C</b>	-20
<b>Min. cable temperature during transport °C</b>	-40

2026-02-25 03:28:40

Technical information	4x16 S PoweRex PE	4x25 S PoweRex PE	4x35 S PoweRex PE	4x50 S PoweRex PE	4x70 S PoweRex PE	4x95 S PoweRex PE	4x120 S PoweRex PE	4x150 S PoweRex PE	4x185 S PoweRex PE	4x240 S PoweRex PE
<b>Product code</b>	<b>1116040</b>	<b>1116041</b>	<b>1116042</b>	<b>1116043</b>	<b>1116044</b>	<b>1116045</b>	<b>1116046</b>	<b>1116047</b>	<b>1116048</b>	<b>1116049</b>
Nominal cable diameter mm	19	22	22	26	29	33	38	42	46	53
Nominal cable weight kg/km	317	458	572	765	1056	1345	1743	2143	2614	3453
Nominal weight of Aluminium kg/km	173	266	364	500	725	961	1265	1554	1886	2547
Nominal Insulation thickness mm	0,7	0,9	0,9	1,0	1,1	1,1	1,2	1,4	1,6	1,7
Nominal thickness of oversheath mm	1,8	1,8	1,8	1,9	2,0	2,1	2,3	2,4	2,6	2,8
<b>Maximum forces during installation when pulling by</b>										
Max. pulling force by pulling-eye kN	1,0	1,5	2,1	3,0	4,2	5,7	7,2	9,0	11,1	14,4
Max. pulling force by pulling-stocking kN	1,0	1,5	2,1	3,0	4,2	5,7	7,2	8,5	8,5	8,5
<b>Minimum bending radii</b>										
Minimum bending radius, handling mm	226	267	266	312	353	394	453	501	553	635
Minimum bending radius, final bending mm	158	187	186	218	247	276	317	351	387	444
<b>Minimum bending radii</b>										
During handling and installation, phase conductor cm	10	13	16	19	23	26	29	32	37	43
During handling and installation, cable cm	23	27	27	31	35	39	45	50	55	63
In final installation, phase conductor cm	7	8	11	13	16	18	20	23	26	30
In final installation, cable cm	16	19	19	22	25	28	32	35	39	44
<b>Minimum bending radii</b>										
During handling and installation, cable m	0,23	0,27	0,27	0,31	0,35	0,39	0,45	0,50	0,55	0,64
In final installation, cable m	0,16	0,19	0,19	0,22	0,25	0,28	0,32	0,35	0,39	0,44
<b>DC resistance</b>										
Max. DC resistance of conductor at 20 °C Ω/km	1,91	1,20	0,868	0,641	0,443	0,320	0,253	0,206	0,164	0,125
<b>Electrical values</b>										
Calculated inductance mH/km	0,29	0,28	0,28	0,28	0,27	0,27	0,26	0,26	0,26	0,25
Calculated operation capacitance µF/km	0,30	0,29	0,29	0,29	0,29	0,29	0,28	0,28	0,28	0,27

2026-02-25 03:28:40

Technical information	4x16 S PoweRex PE	4x25 S PoweRex PE	4x35 S PoweRex PE	4x50 S PoweRex PE	4x70 S PoweRex PE	4x95 S PoweRex PE	4x120 S PoweRex PE	4x150 S PoweRex PE	4x185 S PoweRex PE	4x240 S PoweRex PE
<b>Current ratings</b>										
<b>Cables in air (25 °C)</b>										
two loaded conductor, conductor 70 °C A	76	93	115	140	180	218	254	293	335	395
three loaded conductor, conductor 70 °C A	63	81	100	122	156	190	220	255	291	343
two loaded conductor, conductor 90 °C A	95	112	140	171	219	267	312	360	413	489
three loaded conductor, conductor 90 °C A	80	101	125	152	194	236	274	316	361	425
<b>Cables in air (30 °C)</b>										
two loaded conductor, conductor 70 °C A	73	89	111	135	173	210	244	282	322	380
three loaded conductor, conductor 70 °C A	61	78	96	117	150	183	212	245	280	330
two loaded conductor, conductor 90 °C A	91	108	135	164	211	257	300	346	397	470
three loaded conductor, conductor 90 °C A	77	97	120	146	187	227	263	304	347	409
<b>Cables in the ground (15 °C and 1,0 K.m/W), Installation depth 0,7 m</b>										
Cables in the ground, conductor 65 °C A	78	100	125	150	185	220	255	280	330	375
<b>Cables in the ground (20 °C and 2,5 K.m/W), Installation depth 0,7 m</b>										
Cables in the ground, conductor 90 °C A	64	82	98	117	144	172	197	220	250	290
<b>Maximum thermal short circuit current during 1 s</b>										
Phase (initial 65 °C, final 250 °C) kA	1,7	2,6	3,6	5,2	7,3	9,8	12,4	15,5	19,2	24,9
Phase (initial 90 °C, final 250 °C) kA	1,5	2,4	3,4	4,8	6,7	9,0	11,4	14,2	17,5	22,6
<b>Environmental information</b>										
(A1-A3) GWP emission kgCO2e/km	1843	2868	3696	5110	7229	9648	12233	15150	18580	24698
GWP emissions calculation standard	EN15804:2012 + A2:2019									

2026-02-25 03:28:40

STANDARD PACKAGES	4x16 S PoweRex PE	4x25 S PoweRex PE	4x35 S PoweRex PE	4x50 S PoweRex PE	4x70 S PoweRex PE	4x95 S PoweRex PE	4x120 S PoweRex PE	4x150 S PoweRex PE	4x185 S PoweRex PE	4x240 S PoweRex PE
Product code	1116040	1116041	1116042	1116043	1116044	1116045	1116046	1116047	1116048	1116049
GTIN code	6438176300213	6438176300237	6438176300251	6438176300275	6438176300299	6438176300312	6438176300336	6438176300343	6438176300350	6438176300367
Package	1000 K12	1000 K16	1000 K16	1000 K16	1000 K18	1000 K20	1000 K22	500 K20	500 K22	500 K22
Product code	1116040	1116041	1116042	1116043	1116044	1116045	1116046			
GTIN code	6438176300206	6438176300220	6438176300244	6438176300268	6438176300282	6438176300305	6438176300329			
Package	500 K11	500 K12	500 K12	500 K12	500 K14	500 K16	500 K18			

2026-02-25 03:28:40

Technical information	4x300 S PowerEx PE
<b>Product code</b>	<b>1116050</b>
Nominal cable diameter mm	57
Nominal cable weight kg/km	4177
Nominal weight of Aluminium kg/km	3143
Nominal Insulation thickness mm	1,8
Nominal thickness of oversheath mm	3,0
<b>Maximum forces during installation when pulling by</b>	
Max. pulling force by pulling-eye kN	18,0
Max. pulling force by pulling-stocking kN	8,5
<b>Minimum bending radii</b>	
Minimum bending radius, handling mm	680
Minimum bending radius, final bending mm	476
<b>Minimum bending radii</b>	
During handling and installation, phase conductor cm	46
During handling and installation, cable cm	68
In final installation, phase conductor cm	32
In final installation, cable cm	48
<b>Minimum bending radii</b>	
During handling and installation, cable m	0,68
In final installation, cable m	0,48
<b>DC resistance</b>	
Max. DC resistance of conductor at 20 °C Ω/km	0,100
<b>Electrical values</b>	
Calculated inductance mH/km	0,25
Calculated operation capacitance μF/km	0,26

Technical information	4x300 S PoweRex PE
<b>Current ratings</b>	
<b>Cables in air (25 °C)</b>	
two loaded conductor, conductor 70 °C A	457
three loaded conductor, conductor 70 °C A	396
two loaded conductor, conductor 90 °C A	565
three loaded conductor, conductor 90 °C A	490
<b>Cables in air (30 °C)</b>	
two loaded conductor, conductor 70 °C A	439
three loaded conductor, conductor 70 °C A	381
two loaded conductor, conductor 90 °C A	543
three loaded conductor, conductor 90 °C A	471
<b>Cables in the ground (15 °C and 1,0 K.m/W), Installation depth 0,7 m</b>	
Cables in the ground, conductor 65 °C A	430
<b>Cables in the ground (20 °C and 2,5 K.m/W), Installation depth 0,7 m</b>	
Cables in the ground, conductor 90 °C A	326
<b>Maximum thermal short circuit current during 1 s</b>	
Phase (initial 65 °C, final 250 °C) kA	31,1
Phase (initial 90 °C, final 250 °C) kA	28,2
<b>Environmental information</b>	
(A1-A3) GWP emission kgCO <sub>2</sub> e/km	29975
GWP emissions calculation standard	EN15804:2012 + A2:2019

2026-02-25 03:28:40

STANDARD PACKAGES	4x300 S PoweRex PE
Product code	1116050
GTIN code	6438176300374
Package	500 K26