

AXMK/PE PoweRex PE

Aluminium power cable

0,6/1 (1,2) kV



Application

Aluminium power cable for fixed installations outdoors. May be buried directly in soil, also by ploughing. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free, but without fire protection. The cable is not CPR-classified.

Design

Standards	SFS 5800, SEK TS 424 14 18-1, HD 603 5 E & O
Certificates	SGS Fimko FI 41546
Product Environmental Profile (PEP/EPD)	PEP NXNS-00450-V01.01-EN
Conductor	16-25 mm ² circular stranded aluminium, EN/IEC 60228 class 2 35-300 mm ² sector shaped, stranded aluminium, EN/IEC 60228 class 2
Insulation	UV-protected cross-linked polyethylene XLPE
Core Identification	Yellow-green, brown, black, grey
Inner covering	Plastic tape
Oversheath	UV-protected polyethylene compound PELLD , Black
Rip cord	Aramid cord

Temperature limits

Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during operation °C	-50
Min. cable temperature during handling °C	-20
Min. cable temperature during transport °C	-40

2026-07-10 12:49:05

Technical information	4x16 S PoweRex PE	4x25 S PoweRex PE	4x35 S PoweRex PE	4x50 S PoweRex PE	4x70 S PoweRex PE	4x95 S PoweRex PE	4x120 S PoweRex PE	4x150 S PoweRex PE	4x185 S PoweRex PE	4x240 S PoweRex PE
Product code	1116040	1116041	1116042	1116043	1116044	1116045	1116046	1116047	1116048	1116049
Nominal cable diameter mm	19	22	22	26	29	33	38	42	46	53
Nominal cable weight kg/km	317	458	572	765	1056	1345	1743	2143	2614	3453
Nominal weight of Aluminium kg/km	173	266	364	500	725	961	1265	1554	1886	2547
Nominal Insulation thickness mm	0,7	0,9	0,9	1,0	1,1	1,1	1,2	1,4	1,6	1,7
Nominal thickness of oversheath mm	1,8	1,8	1,8	1,9	2,0	2,1	2,3	2,4	2,6	2,8
Maximum forces during installation when pulling by										
Max. pulling force by pulling-eye kN	1,0	1,5	2,1	3,0	4,2	5,7	7,2	9,0	11,1	14,4
Max. pulling force by pulling-stocking kN	1,0	1,5	2,1	3,0	4,2	5,7	7,2	8,5	8,5	8,5
Minimum bending radii										
Minimum bending radius, handling mm	226	267	266	312	353	394	453	501	553	635
Minimum bending radius, final bending mm	158	187	186	218	247	276	317	351	387	444
Minimum bending radii										
During handling and installation, phase conductor cm	10	13	16	19	23	26	29	32	37	43
During handling and installation, cable cm	23	27	27	31	35	39	45	50	55	63
In final installation, phase conductor cm	7	8	11	13	16	18	20	23	26	30
In final installation, cable cm	16	19	19	22	25	28	32	35	39	44
Minimum bending radii										
During handling and installation, cable m	0,23	0,27	0,27	0,31	0,35	0,39	0,45	0,50	0,55	0,64
In final installation, cable m	0,16	0,19	0,19	0,22	0,25	0,28	0,32	0,35	0,39	0,44
DC resistance										
Max. DC resistance of conductor at 20 °C Ω/km	1,91	1,20	0,868	0,641	0,443	0,320	0,253	0,206	0,164	0,125
Electrical values										
Calculated inductance mH/km	0,29	0,28	0,28	0,28	0,27	0,27	0,26	0,26	0,26	0,25
Calculated operation capacitance µF/km	0,30	0,29	0,29	0,29	0,29	0,29	0,28	0,28	0,28	0,27

2026-07-10 12:49:05

Technical information	4x16 S PoweRex PE	4x25 S PoweRex PE	4x35 S PoweRex PE	4x50 S PoweRex PE	4x70 S PoweRex PE	4x95 S PoweRex PE	4x120 S PoweRex PE	4x150 S PoweRex PE	4x185 S PoweRex PE	4x240 S PoweRex PE
Current ratings										
Cables in air (25 °C)										
two loaded conductor, conductor 70 °C A	76	93	115	140	180	218	254	293	335	395
three loaded conductor, conductor 70 °C A	63	81	100	122	156	190	220	255	291	343
two loaded conductor, conductor 90 °C A	95	112	140	171	219	267	312	360	413	489
three loaded conductor, conductor 90 °C A	80	101	125	152	194	236	274	316	361	425
Cables in air (30 °C)										
two loaded conductor, conductor 70 °C A	73	89	111	135	173	210	244	282	322	380
three loaded conductor, conductor 70 °C A	61	78	96	117	150	183	212	245	280	330
two loaded conductor, conductor 90 °C A	91	108	135	164	211	257	300	346	397	470
three loaded conductor, conductor 90 °C A	77	97	120	146	187	227	263	304	347	409
Cables in the ground (15 °C and 1,0 K.m/W), Installation depth 0,7 m										
Cables in the ground, conductor 65 °C A	78	100	125	150	185	220	255	280	330	375
Cables in the ground (20 °C and 2,5 K.m/W), Installation depth 0,7 m										
Cables in the ground, conductor 90 °C A	64	82	98	117	144	172	197	220	250	290
Maximum thermal short circuit current during 1 s										
Phase (initial 65 °C, final 250 °C) kA	1,7	2,6	3,6	5,2	7,3	9,8	12,4	15,5	19,2	24,9
Phase (initial 90 °C, final 250 °C) kA	1,5	2,4	3,4	4,8	6,7	9,0	11,4	14,2	17,5	22,6
Environmental information										
(A1-A3) GWP emission kgCO2e/km	1843	2868	3696	5110	7229	9648	12233	15150	18580	24698
GWP emissions calculation standard	EN15804:2012 + A2:2019	EN15804:2012 + A2:2019	EN15804:2012 + A2:2019	EN15804:2012 + A2:2019	EN15804:2012 + A2:2019	EN15804:2012 + A2:2019	EN15804:2012 + A2:2019	EN15804:2012 + A2:2019	EN15804:2012 + A2:2019	EN15804:2012 + A2:2019

2026-07-10 12:49:05

STANDARD PACKAGES	4x16 S PoweRex PE	4x25 S PoweRex PE	4x35 S PoweRex PE	4x50 S PoweRex PE	4x70 S PoweRex PE	4x95 S PoweRex PE	4x120 S PoweRex PE	4x150 S PoweRex PE	4x185 S PoweRex PE	4x240 S PoweRex PE
Product code	1116040	1116041	1116042	1116043	1116044	1116045	1116046	1116047	1116048	1116049
GTIN code	6438176300213	6438176300237	6438176300251	6438176300275	6438176300299	6438176300312	6438176300336	6438176300343	6438176300350	6438176300367
Package	1000 K12	1000 K16	1000 K16	1000 K16	1000 K18	1000 K20	1000 K22	500 K20	500 K22	500 K22
Product code	1116040	1116041	1116042	1116043	1116044	1116045	1116046			
GTIN code	6438176300206	6438176300220	6438176300244	6438176300268	6438176300282	6438176300305	6438176300329			
Package	500 K11	500 K12	500 K12	500 K12	500 K14	500 K16	500 K18			

Technical information	4x300 S PowerEx PE
Product code	1116050
Nominal cable diameter mm	57
Nominal cable weight kg/km	4177
Nominal weight of Aluminium kg/km	3143
Nominal Insulation thickness mm	1,8
Nominal thickness of oversheath mm	3,0
Maximum forces during installation when pulling by	
Max. pulling force by pulling-eye kN	18,0
Max. pulling force by pulling-stocking kN	8,5
Minimum bending radii	
Minimum bending radius, handling mm	680
Minimum bending radius, final bending mm	476
Minimum bending radii	
During handling and installation, phase conductor cm	46
During handling and installation, cable cm	68
In final installation, phase conductor cm	32
In final installation, cable cm	48
Minimum bending radii	
During handling and installation, cable m	0,68
In final installation, cable m	0,48
DC resistance	
Max. DC resistance of conductor at 20 °C Ω/km	0,100
Electrical values	
Calculated inductance mH/km	0,25
Calculated operation capacitance μF/km	0,26

Technical information	4x300 S PowerEx PE
Current ratings	
Cables in air (25 °C)	
two loaded conductor, conductor 70 °C A	457
three loaded conductor, conductor 70 °C A	396
two loaded conductor, conductor 90 °C A	565
three loaded conductor, conductor 90 °C A	490
Cables in air (30 °C)	
two loaded conductor, conductor 70 °C A	439
three loaded conductor, conductor 70 °C A	381
two loaded conductor, conductor 90 °C A	543
three loaded conductor, conductor 90 °C A	471
Cables in the ground (15 °C and 1,0 K.m/W), Installation depth 0,7 m	
Cables in the ground, conductor 65 °C A	430
Cables in the ground (20 °C and 2,5 K.m/W), Installation depth 0,7 m	
Cables in the ground, conductor 90 °C A	326
Maximum thermal short circuit current during 1 s	
Phase (initial 65 °C, final 250 °C) kA	31,1
Phase (initial 90 °C, final 250 °C) kA	28,2
Environmental information	
(A1-A3) GWP emission kgCO ₂ e/km	29975
GWP emissions calculation standard	EN15804:2012 + A2:2019

2026-07-10 12:49:05

STANDARD PACKAGES	4x300 S PoweRex PE
Product code	1116050
GTIN code	6438176300374
Package	500 K26