MMJ-HF

Installation cable HF

450/750 V

Installation cable for fixed installations indoors and outdoors. Not to be laid in soil nor directly in cast concrete. Can be embedded to the groove filled with plaster. UV-protected oversheath and core insulation. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Dca-s2,d2,a2.

Standards	SFS 5544, NEK 591
Reaction to fire	Dca-s2,d2,a2; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Circular stranded copper, EN/IEC 60228 class 2
Insulation	Polyethylene compound
Core identification	Yellowgreen, blue, brown, black, grey
Oversheath	UV-protected polyolefin compound, White
Product code	1145078
Size	5x10 S
Nominal cable diameter mm	22
Nominal cable weight kg/km	865
During handling and installation, cable cm	22
In final installation, cable cm	6
Max. DC resistance of conductor at 20 °C Ω/km	1,83
Max. conductor temperature °C	70
Max. cond. temp. short circuit max. 5 s °C	160
Min. cable temperature during handling °C	-15
standard packing m	Drum 250
Electricity number	6410004164464
EAN code	6410004164464

© **Reka** rights for changes reserved • **www.rekacables.com** •