


FRHF-EMC / BFSI-EMC

Copper power cable EMC FRHF

0.6/1 (1.2) kV



Fire-resistant EMC power cable for fixed installations indoors and outdoors. May be buried directly in soil. EMC shielded cable gives an excellent protection against electromagnetic disturbances. For locations where safety requires the operation of alarm, control, signalling and energy circuits also during a fire. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. No requirement for CPR-classification.

Additional information	IEC 60331-21 Fire resistant, 180 min. IEC 60331-1, -2 EN 50200, EN 50362 Fire resistant with shock, 90 min. EN/IEC 60332-3-22 Flame retardant in a bunch, Category A EN/IEC 61034 Low smoke density EN/IEC 60754 Halogen-free, non-corrosive EN 50289-1-6 Electromagnetic performance
Standards	SFS 5547, HD 604 5 D
Conductor	1,5-6 mm ² circular solid copper, EN/IEC 60228 class 1 10-25 mm ² circular stranded copper, EN/IEC 60228 class 2 35-240 mm ² sector shaped stranded copper, EN/IEC 60228 class 2
Insulation	Halogen-free XLPE, mica tape
Core identification	Blue, brown, black, grey
Oversheath	UV-protected halogen-free polyolefin compound , Orange
Size	4x35/16
Product code	1146667
Voltage	0.6/1 (1.2) kV
Nominal diameter of complete cable mm	29
Nominal weight of cable kg/km	1940
Max. pulling force by pulling-eye kN	2.1
Max. DC resistance of conductor at 20 °C Ω/km	0,524
Min. cable temperature during handling °C	-15
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
standard packing m	Drum 1000
Electricity number	6410006022007
EAN code	6410006022007

