2026-11-09 08:56:29

AHXAMK-WM 12/20 (24) kV 3-core

Medium voltage cable

12/20 (24) kV



Medium-voltage cable for fixed installations outdoors. May be buried directly in soil, also by ploughing. Cable is longitudinally and radially watertight and therefore it is suitable where wet soil and / or fresh water permanently occurs. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free, but without fire protection. The cable is not CPR-classified.

Standards	HD 620 10 F, SFS 5636
Conductor	Watertight, circular, stranded aluminium, EN/IEC 60228 class 2
Insulation	Cross-linked polyethylene XLPE
Oversheath	UV-protected PE-plastic PELLD, Black
Product code	1187144
Size	3x95+62
Nominal cable diameter mm	72
Nominal cable weight kg/km	2882
During handling and installation, cable cm	86
In final installation, cable cm	60
Max. DC resistance of conductor at 20 °C Ω/km	0,320
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-20
standard packing m	Drum 500
Electricity number	6410006022465
EAN code	6410006022465

© **Reka** rights for changes reserved • **www.rekacables.com** •

MADE IN FINLAND