

MCMO

Control cable

450/750 V



Control cable for fixed installations indoors and outdoors. May be buried directly in soil. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. The cable is flame-retardant according to CPR-class Eca.

| | |
|---|---|
| Standards | HD 627 4 D 2, SFS 3713 |
| Reaction to fire | Eca; EN 13501-6, EN 50575:2014+A1:2016 |
| Conductor | Circular solid copper, EN/IEC 60228 class 1 |
| Insulation | PVC-compound |
| Core identification | Black insulation, white numbers |
| Oversheath | UV-protected PVC-compound, Black |
| Size | 7x1,5/6 |
| Product code | 1108207 |
| Nominal cable diameter mm | 12 |
| Nominal cable weight kg/km | 272 |
| During handling and installation, cable cm | 13 |
| In final installation, cable cm | 10 |
| Max. DC resistance of conductor at 20 °C Ω /km | 12,1 |
| Max. conductor temperature °C | 70 |
| Max. cond. temp. short circuit max. 5 s °C | 160 |
| Min. cable temperature during handling °C | -15 |
| standard packing m | Drum 500 |
| Electricity number | 6410006029273 |
| EAN code | 6410006029273 |