

## MCMO

## Control cable

## 450/750 V



Control cable for fixed installations indoors and outdoors. May be buried directly in soil. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. The cable is flame-retardant according to CPR-class Eca.

|   |   |
|---|---|
| Standards                                     | HD 627 4 D 2, SFS 3719                      |
| Reaction to fire                              | Eca; EN 13501-6, EN 50575:2014+A1:2016      |
| Conductor                                     | Circular solid copper, EN/IEC 60228 class 1 |
| Insulation                                    | PVC-compound                                |
| Core identification                           | Black insulation, white numbers             |
| Oversheath                                    | UV-protected PVC-compound, Black            |
| Size  | 12x2,5/6                                    |
| Product code                                  | 1108262                                     |
| Nominal cable diameter mm                     | 18  |
| Nominal cable weight kg/km                    | 559   |
| During handling and installation, cable cm    | 19  |
| In final installation, cable cm               | 15  |
| Max. DC resistance of conductor at 20 °C Ω/km | 7,41  |
| Max. conductor temperature °C                 | 70  |
| Max. cond. temp. short circuit max. 5 s °C    | 160   |
| Min. cable temperature during handling °C     | -15   |
| standard packing m                            | Drum 1000                                   |
| Electricity number                            | 6410006029334                               |
| EAN code                                      | 6410006029334                               |