
# MCMO

## Control cable

## 450/750 V




Control cable for fixed installations indoors and outdoors. May be buried directly in soil. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. The cable is flame-retardant according to CPR-class Eca.

| | |
|---|---|
| **Standards** | HD 627 4 D 2, SFS 3713 |
| **Reaction to fire** | Eca; EN 13501-6, EN 50575:2014+A1:2016 |
| **Conductor** | Circular solid copper, EN/IEC 60228 class 1 |
| **Insulation** | PVC-compound |
| **Core identification** | Black insulation, white numbers |
| **Oversheath** | UV-protected PVC-compound, Black |
| **Product code** | 1108277 |
| **Size** | 27x2,5/10 |
| **Nominal cable diameter mm** | 26 |
| **Nominal cable weight kg/km** | 1134 |
| **During handling and installation, cable cm** | 31 |
| **In final installation, cable cm** | 22 |
| **Max. DC resistance of conductor at 20 °C Ω/km** | 7,41 |
| **Max. conductor temperature °C** | 70 |
| **Max. cond. temp. short circuit max. 5 s °C** | 160 |
| **Min. cable temperature during handling °C** | -15 |
| **standard packing m** | Drum 500 |
| **Electricity number** | 6410006029419 |
| **EAN code** | 6410006029419 |

© **Reka** rights for changes reserved • **www.rekacables.com** •