ISO 45001, ISO 14001 and ISO 9001 certified company
REACH and RoHS compliant products

2026-11-09 16:59:21

MCMK

Copper power cable

0,6/1 (1,2) kV



Copper power cable for fixed installations indoors and outdoors. May be buried directly in soil or cast concrete. Installations must be in accordance with national regulations and rules of installations. The cable is flame-retardant according to CPR-class Eca.

Standards	SFS 4880, SEK TS 424 14 18-1, HD 603 3 F & L
Reaction to fire	Eca; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Circular solid copper, EN/IEC 60228 class 1
Insulation	PVC-compound
Core identification	Blue, brown
Oversheath	UV-protected PVC-compound, Black
Product code	1106106
Size	2x2,5/2,5
Nominal cable diameter mm	12
Nominal cable weight kg/km	219
During handling and installation, cable cm	15
In final installation, cable cm	10
Max. DC resistance of conductor at 20 °C Ω/km	7,41
Max. conductor temperature °C	70
Max. cond. temp. short circuit max. 5 s °C	160
Min. cable temperature during handling °C	-15
standard packing m	Bundle 100
Electricity number	6410006031139
EAN code	6410006031139

© **Reka** rights for changes reserved • **www.rekacables.com** •