2026-11-09 08:34:19

AXMK 1-core

Aluminium power cable

0,6/1 (1,2) kV

Aluminium power cable for fixed installations indoors and outdoors. The cable is not intended for underground installations. UV-protected oversheath and core insulation. Installations must be in accordance with national regulations and rules of installations. The cable is flame-retardant according to CPR-class Eca.

Standards	SFS 4879, SEK TS 424 14 18-1, HD 603 5 D & O
Reaction to fire	Eca; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Circular stranded aluminium, EN/IEC 60228 class 2
Insulation	UV-protected cross-linked polyethylene XLPE
Core identification	Black
Oversheath	UV-protected PVC-compound, Black
Product code	1116020
Size	1x300
Nominal cable diameter mm	28
Nominal cable weight kg/km	1178
During handling and installation, cable cm	42
In final installation, cable cm	29
Max. DC resistance of conductor at 20 °C Ω/km	0,100
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-20
standard packing m	Drum 500
Electricity number	6410006262007
EAN code	6410006262007

© **Reka** rights for changes reserved • **www.rekacables.com** •