# AXLJ-F TT 12/20 (24) kV 3x1 core CAS

## Medium voltage cable

## 12/20 (24) kV

Medium-voltage cable for fixed installations outdoors. May be buried directly in soil, also by ploughing. Cable is longitudinally and radially watertight and therefore it is suitable where wet soil and / or fresh water permanently occurs. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free, but without fire protection. The cable is not CPR-classified.

| | |
|---|---|
| **Standards** | HD 620 10 M, SS 424 14 16 |
| **Conductor** | Watertight, circular, stranded aluminium, EN/IEC 60228 class 2 |
| **Insulation** | Cross-linked polyethylene XLPE |
| **Oversheath** | UV-protected PE-plastic PELLD, Black |
| **Product code** | 1181304 |
| **Size** | 3x1x95/16 CAS |
| **Nominal cable diameter mm** | 66 |
| **Nominal cable weight kg/km** | 2670 |
| **During handling and installation, cable cm** | 79 |
| **In final installation, cable cm** | 55 |
| **Max. DC resistance of conductor at 20 °C Ω/km** | 0,320 |
| **Max. conductor temperature °C** | 90 |
| **Max. cond. temp. short circuit max. 5 s °C** | 250 |
| **Min. cable temperature during handling °C** | -20 |
| **standard packing m** | Drum 500 |
| **Electricity number** | 6410006275069 |
| **EAN code** | 6410006275069 |

© **Reka** rights for changes reserved • **www.rekacables.com** •

MADE IN FINLAND