EMCMK-HF D / FXQJ-EMC D / IFSI-EMC-Cu D



Copper power cable EMC

0,6/1 (1,2) kV

Copper power cable for fixed installations indoors and outdoors. May be buried directly in soil. EMC shielded cable gives an excellent protection against electromagnetic disturbancies. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Dca-s2,d2,a2.

Standards	SFS 5546, SEK TS 424 14 18-1, HD 604 5 I & D, IEC 60502-1
Reaction to fire	Dca-s2,d2,a2; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Sector shaped stranded copper, EN/IEC 60228 class 2
Insulation	Cross-linked polyethylene XLPE
Core identification	Brown, black, grey
Oversheath	UV-protected polyolefin compound, Black
Product code	1256654
Size	3x240/120
Nominal cable diameter mm	51
Nominal cable weight kg/km	8535
During handling and installation, cable cm	61
In final installation, cable cm	43
Max. DC resistance of conductor at 20 °C Ω/km	0,0754
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-15
standard packing m	Drum 500
Electricity number	6438176115824
EAN code	6438176115824

© **Reka** rights for changes reserved • **www.rekacables.com** •