
AEMCMK-HF / AXQJ-EMC / IFSI-EMC-Al

Aluminium power cable EMC

0,6/1 (1,2) kV



Aluminium power cable for fixed installations indoors and outdoors. May be buried directly in soil. EMC shielded cable gives an excellent protection against electromagnetic disturbancies. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Dca-s2,d2,a2.

Standards	SFS 5546, SEK TS 424 14 18-1, HD 604 5 I & D, IEC 60502-1
Reaction to fire	Dca-s2,d2,a2; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Circular stranded aluminium, EN/IEC 60228 class 2
Insulation	Cross-linked polyethylene XLPE
Core identification	Brown, black, grey
Oversheath	UV-protected polyolefin compound, Black
Product code	1149200
Size	3x16/10
Nominal cable diameter mm	21
Nominal cable weight kg/km	610
During handling and installation, cable cm	25
In final installation, cable cm	17
Max. DC resistance of conductor at 20 °C Ω/km	1,91
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-15
standard packing m	Drum 500
Electricity number	6438176225653
EAN code	6438176225653

© **Reka** rights for changes reserved • **www.rekacables.com** •