2026-11-23 07:50:47

# AXQJ-F D / AHXCMK-HF D 12/20 (24) kV 3-core BK

## Medium voltage cable

## 12/20 (24) kV




Medium-voltage cable for fixed installations indoors and outdoors. May be buried directly in soil. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Dca-s2,d2,a2.

| | |
|---|---|
| **Standards** | HD 620 10 M & F, SS 424 14 16, SFS 5636 |
| **Reaction to fire** | Dca-s2,d2,a2; EN 13501-6, EN 50575:2014+A1:2016 |
| **Conductor** | Watertight, circular, stranded aluminium, EN/IEC 60228 class 2 |
| **Insulation** | Cross-linked polyethylene XLPE |
| **Oversheath** | UV-protected halogen-free polyolefin compound, Black |
| **Product code** | 1181851 |
| **Size** | 3x95/25 BK |
| **Nominal cable diameter mm** | 58 |
| **Nominal cable weight kg/km** | 2734 |
| **During handling and installation, cable cm** | 70 |
| **In final installation, cable cm** | 49 |
| **Max. DC resistance of conductor at 20 °C Ω/km** | 0.32 |
| **Max. conductor temperature °C** | 90 |
| **Max. cond. temp. short circuit max. 5 s °C** | 250 |
| **Min. cable temperature during handling °C** | -15 |
| **standard packing m** | Drum 1000 |
| **Electricity number** | 6438176229453 |
| **EAN code** | 6438176229453 |

© **Reka** rights for changes reserved • **www.rekacables.com** •