2026-11-23 07:50:47

AXQJ-F D / AHXCMK-HF D 12/20 (24) kV 3-core BK



Medium voltage cable

12/20 (24) kV

Medium-voltage cable for fixed installations indoors and outdoors. May be buried directly in soil. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Dca-s2,d2,a2.

Standards	HD 620 10 M & F, SS 424 14 16, SFS 5636
Reaction to fire	Dca-s2,d2,a2; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Watertight, circular, stranded aluminium, EN/IEC 60228 class 2
Insulation	Cross-linked polyethylene XLPE
Oversheath	UV-protected halogen-free polyolefin compound, Black
Product code	1181859
Size	3x240/35 BK
Nominal cable diameter mm	74
Nominal cable weight kg/km	4786
During handling and installation, cable cm	89
In final installation, cable cm	63
Max. DC resistance of conductor at 20 °C Ω/km	0,125
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-15
standard packing m	Drum 500
Electricity number	6438176229507
EAN code	6438176229507

© **Reka** rights for changes reserved • **www.rekacables.com** •