

AXMK/PE PoweRex PE

Aluminium power cable

0,6/1 (1,2) kV



Aluminium power cable for fixed installations outdoors. May be buried directly in soil, also by ploughing. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free, but without fire protection. The cable is not CPR-classified.

Standards	SFS 5800, SEK TS 424 14 18-1, HD 603 5 E & O
Product Environmental Profile (PEP/EPD)	PEP NXNS-00450-V01.01-EN
(A1-A3) GWP emission kgCO₂e/km	2868
Conductor	Circular stranded aluminium, EN/IEC 60228 class 2
Insulation	UV-protected cross-linked polyethylene XLPE
Core identification	Yellowgreen, brown, black, grey
Oversheath	UV-protected polyethylene compound PELLD, Black
Product code	1116041
Size	4x25 S PoweRex PE
Nominal cable diameter mm	22
Nominal cable weight kg/km	458
During handling and installation, cable cm	27
In final installation, cable cm	19
Max. DC resistance of conductor at 20 °C Ω/km	1,20
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-20
standard packing m	Drum 1000
Electricity number	6438176300237
EAN code	6438176300237