AXCMK-HF C / AXQJ C / IFSI-Al C

Aluminium power cable HF

0,6/1 (1,2) kV



Aluminium power cable for fixed installations indoors and outdoors. May be buried directly in soil. Can also be used in medical facilities where higher fire class is required. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Cca-s1,d1,a1.

Standards	SFS 5546, SEK TS 424 14 18-1, HD 604 5 I & D, IEC 60502-1
Reaction to fire	Cca-s1,d1,a1; EN 13501-6, EN 50575:2014+A1:2016
Product Environmental Profile (PEP/EPD)	PEP NXNS-00560-V01.01-EN
(A1-A3) GWP emission kgCO2e/km	43781
Conductor	Sector shaped stranded aluminium, EN/IEC 60228 class 2
Insulation	Cross-linked polyethylene XLPE
Core identification	Blue, brown, black, grey
Oversheath	UV-protected polyolefin compound, Black
Product code	1149262
Size	4x300/88
Nominal cable diameter mm	60
Nominal cable weight kg/km	5400
During handling and installation, cable cm	72
In final installation, cable cm	51
Max. DC resistance of conductor at 20 °C Ω/km	0,100
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-15
standard packing m	Drum 500
Electricity number	6438176300992
EAN code	6438176300992

© **Reka** rights for changes reserved • **www.rekacables.com** •