
AEMCMK-HF C / AXQJ C / IFSI-EMC-Al C



Aluminium power cable EMC

0,6/1 (1,2) kV

Aluminium power cable for fixed installations indoors and outdoors. May be buried directly in soil. Can also be used in medical facilities where higher fire class is required. EMC shielded cable gives an excellent protection against electromagnetic disturbancies. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Cca-s1,d1,a1.

Standards	SFS 5546, SEK TS 424 14 18-1, HD 604 5 I & D, IEC 60502-1
Reaction to fire	Cca-s1,d1,a1; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Sector shaped stranded aluminium, EN/IEC 60228 class 2
Insulation	Cross-linked polyethylene XLPE
Core identification	Blue, brown, black, grey
Oversheath	UV-protected polyolefin compound, Black
Product code	1149297
Size	4x95/29
Nominal cable diameter mm	35
Nominal cable weight kg/km	1865
During handling and installation, cable cm	42
In final installation, cable cm	30
Max. DC resistance of conductor at 20 °C Ω/km	0,320
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-15
standard packing m	Drum 1000
Electricity number	6438176303047
EAN code	6438176303047

© **Reka** rights for changes reserved • **www.rekacables.com** •