


EMCMK-HF C / FXQJ-EMC C /
IFSI-EMC-Cu C

Copper power cable EMC

0,6/1 (1,2) kV



Copper power cable for fixed installations indoors and outdoors. May be buried directly in soil. Can also be used in medical facilities where higher fire class is required. EMC shielded cable gives an excellent protection against electromagnetic disturbances. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Cca-s1,d1,a1.

Standards	SFS 5546, SEK TS 424 14 18-1, HD 604 5 I & D, IEC 60502-1
Reaction to fire	Cca-s1,d1,a1; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Sector shaped stranded copper, EN/IEC 60228 class 2
Insulation	Cross-linked polyethylene XLPE
Core identification	Brown, black, grey
Oversheath	UV-protected polyolefin compound, Black
Size	3x95/50
Product code	1146780
Nominal cable diameter mm	33
Nominal cable weight kg/km	3475
During handling and installation, cable cm	40
In final installation, cable cm	28
Max. DC resistance of conductor at 20 °C Ω/km	0,193
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-15
standard packing m	Drum 1000
Electricity number	6438176303313
EAN code	6438176303313