ISO 45001, ISO 14001 and ISO 9001 certified company
REACH and RoHS compliant products

2026-10-05 18:11:25

FRHF-XCMK / BFSI

Copper power cable FRHF

0,6/1 (1,2) kV

Fire-resistant power cable for fixed installations indoors and outdoors. May be buried directly in soil. For locations where safety requires the operation of alarm, control, signalling and energy circuits also during a fire. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. No requirement for CPR-classification.

Additional information	IEC 60331-21 Fire-resistant, 180 min. IEC 60331-1, -2 EN 50200, EN 50362 Fire-resistant with shock, 90 min. EN/IEC 60332-3-24 Flame retardant in a bunch, Category C EN/IEC 61034 Low smoke density EN/IEC 60754 Halogen-free, non-corrosive
Standards	SFS 5547, HD 604 5 D
Conductor	Sector shaped stranded copper, EN/IEC 60228 class 2
Insulation	Cross-linked polyethylene XLPE and mica-tape
Core identification	Brown, black, grey
Oversheath	UV-protected polyolefin compound, Orange
Product code	1146828
Size	3x70/35
Nominal cable diameter mm	34
Nominal cable weight kg/km	2888
During handling and installation, cable cm	41
In final installation, cable cm	28
Max. DC resistance of conductor at 20 °C Ω/km	0,268
Max. conductor temperature °C	90
Max. cond. temp. short circuit max. 5 s °C	250
Min. cable temperature during handling °C	-15
standard packing m	Drum 500
Electricity number	6438176307854
EAN code	6438176307854

© **Reka** rights for changes reserved • **www.rekacables.com** •