

## FRHF-XCMK / BFSI

### Copper power cable FRHF

### 0,6/1 (1,2) kV



Fire-resistant power cable for fixed installations indoors and outdoors. May be buried directly in soil. For locations where safety requires the operation of alarm, control, signalling and energy circuits also during a fire. The conductor insulation must be protected against UV-radiation. Installations must be in accordance with national regulations and rules of installations. No requirement for CPR-classification.

|                                                      |                                                                                                                                                                                                                                                          |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Additional information</b>                        | IEC 60331-21 Fire-resistant, 180 min.<br>IEC 60331-1, -2 EN 50200, EN 50362 Fire-resistant with shock, 90 min.<br>EN/IEC 60332-3-24 Flame retardant in a bunch, Category C<br>EN/IEC 61034 Low smoke density<br>EN/IEC 60754 Halogen-free, non-corrosive |
| <b>Standards</b>                                     | SFS 5547, HD 604 5 D                                                                                                                                                                                                                                     |
| <b>Conductor</b>                                     | Circular stranded copper, EN/IEC 60228 class 2                                                                                                                                                                                                           |
| <b>Insulation</b>                                    | Cross-linked polyethylene XLPE and mica-tape                                                                                                                                                                                                             |
| <b>Core identification</b>                           | Blue, brown, black, grey                                                                                                                                                                                                                                 |
| <b>Oversheath</b>                                    | UV-protected polyolefin compound, Orange                                                                                                                                                                                                                 |
| <b>Product code</b>                                  | 1146839                                                                                                                                                                                                                                                  |
| <b>Size</b>                                          | 4x10/10                                                                                                                                                                                                                                                  |
| <b>Nominal cable diameter mm</b>                     | 21                                                                                                                                                                                                                                                       |
| <b>Nominal cable weight kg/km</b>                    | 832                                                                                                                                                                                                                                                      |
| <b>During handling and installation, cable cm</b>    | 26                                                                                                                                                                                                                                                       |
| <b>In final installation, cable cm</b>               | 18                                                                                                                                                                                                                                                       |
| <b>Max. DC resistance of conductor at 20 °C Ω/km</b> | 1,83                                                                                                                                                                                                                                                     |
| <b>Max. conductor temperature °C</b>                 | 90                                                                                                                                                                                                                                                       |
| <b>Max. cond. temp. short circuit max. 5 s °C</b>    | 250                                                                                                                                                                                                                                                      |
| <b>Min. cable temperature during handling °C</b>     | -15                                                                                                                                                                                                                                                      |
| <b>standard packing m</b>                            | Drum 500                                                                                                                                                                                                                                                 |
| <b>Electricity number</b>                            | 6438176307953                                                                                                                                                                                                                                            |
| <b>EAN code</b>                                      | 6438176307953                                                                                                                                                                                                                                            |