2026-11-12 12:55:19

MKEM-HF C / H07Z1-K

Installation wire-HF

450/750 V



Installation wire for fixed installations indoors and outdoors. Not to be laid in soil nor directly in cast concrete. Can also be used in medical facilities where higher fire class is required. Installations must be in accordance with national regulations and rules of installations. The cable is halogen-free and flame-retardant according to CPR-class Cca-s1,d1,a1.

Standards	EN 50525-3-31
Reaction to fire	Cca-s1,d1,a1; EN 13501-6, EN 50575:2014+A1:2016
Conductor	Circular flexible copper, EN/IEC 60228 class 5
Insulation	UV-protected polyolefin compound
Core identification	Yellowgreen
Product code	1140148
Size	35 GNYE H07Z1-K
Nominal cable diameter mm	10
Nominal cable weight kg/km	355
During handling and installation, cable cm	8
In final installation, cable cm	3
Max. DC resistance of conductor at 20 °C Ω/km	0,554
Max. conductor temperature °C	70
Max. cond. temp. short circuit max. 5 s °C	160
Min. cable temperature during handling °C	-15
standard packing m	Bundle 50
Electricity number	6438176308417
EAN code	6438176308417

© **Reka** rights for changes reserved • **www.rekacables.com** •