

## MKEM-HF Installation wire 35 BK

Conductor may be laid indoors in dry situations. For installation in conduits, for internal wiring in electrical equipments. Where needed halogen free, non corrosive gases and low smoke density cables.



<b>Special property</b>	Flame retardant EN 60332-3-23, halogen free EN 60754-2, low smoke EN 61034-2
<b>Fire class</b>	Dca-s2, d2, a2
<b>CPR - DoP</b>	<a href="#">2017045_DOP.pdf</a> <a href="#">2017046_DOP.pdf</a>
<b>Conductor</b>	Circular, flexible copper
<b>Insulation</b>	Halogen free polyolefin

Size: 35 BK  
Reka code: 1145923--en  
Packing (m): 500 K7

<b>Voltage</b>	450/750 V
<b>Diameter (mm)</b>	11
<b>Weight&amp;nbsp;nbsp;</b>	360
<b>Minimum allowed bending radius in installation (cm)</b>	9
<b>Minimum allowed bending radius in final installation (cm)</b>	3
<b>Maximum DC resistance of phase conductor, +20°C (ohm/km)</b>	524
<b>Minimum handling temperature (°C)</b>	-15
<b>Maximum conductor temperature (°C)</b>	70

<b>Conductor short-circuit temperature, 5 s (°C)</b>	160
<b>Product number</b>	04 005 13
<b>GTIN code</b>	



Saved from [www.rekacables.com](http://www.rekacables.com) website 21.10.2018. Please note that product details can change.