

## MKEM-HF Installation wire 35 YE/GN

Conductor may be laid indoors in dry situations. For installation in conduits, for internal wiring in electrical equipments. Where needed halogen free, non corrosive gases and low smoke density cables.



<b>Special property</b>	Flame retardant EN 60332-3-23, halogen free EN 60754-2, low smoke EN 61034-2
<b>Fire class</b>	Dca-s2, d2, a2
<b>CPR - DoP</b>	<a href="#">2017045_DOP.pdf</a> <a href="#">2017046_DOP.pdf</a>
<b>Conductor</b>	Circular, flexible copper
<b>Insulation</b>	Halogen free polyolefin

Size: 35 YE/GN  
Reka code: 1145928--en  
Packing (m): 500 K7

<b>Voltage</b>	450/750 V
<b>Diameter (mm)</b>	11
<b>Weight&amp;nbsp;nbsp;</b>	360
<b>Minimum allowed bending radius in installation (cm)</b>	9
<b>Minimum allowed bending radius in final installation (cm)</b>	3
<b>Maximum DC resistance of phase conductor, +20°C (ohm/km)</b>	524
<b>Minimum handling temperature (°C)</b>	-15
<b>Maximum conductor temperature (°C)</b>	70

<b>Conductor short-circuit temperature, 5 s (°C)</b>	160
<b>Product number</b>	04 005 18
<b>GTIN code</b>	



Saved from [www.rekacables.com](http://www.rekacables.com) website 21.10.2018. Please note that product details can change.